

**Product / brand:** CyclusPrint Heavy Weights

**Paper Mill:** Bessé sur Braye

**Country of origin:** France

**Website:** [www.arjowigginsgraphic.com](http://www.arjowigginsgraphic.com)



## Product Data

---

CyclusPrint heavy weights is a 100% recycled matt-coated, natural white fine printing paper for use in both full colour and black and white printing. The non-reflective matt surface is especially suitable for publications with a combination of large text areas and high quality pictures.

- CyclusPrint heavy weights is available in the following weights: 250, 300 and 350gsm  
For CyclusPrint lighter weights – please see separate technical sheet.

## Certified Management Systems & Product certifications

---

For more in-depth environmental information, please request the Environmental Declaration or visit [www.arjowigginsgraphic.com](http://www.arjowigginsgraphic.com)

- ISO 9001 Quality management
- ISO 14001 Environmental Management Standard
- OHSAS 18001 Health and Safety Management System
- EU Ecolabel Certification
- Blue Angel
- DIN 6738 Permanent Paper Standard
- National Association of Paper Merchants (NAPM)

## Applications

---

Suitable for a range of applications (depending on grammage):  
Covers for books, magazines, reports and brochures. Calendars, posters, greeting cards, business cards, invitations etc.

## Recommendations

---

**Printing processes:**

- Offset, dry offset and web offset with heatset drying
- Printing inks : all inks suitable for coated paper

**Converting:**

- Suitable for folding and punching, precreasing required. Clamps, thread and adhesive binding.
- Recommended - lamination and varnishing

## Technical specification

---

If you seek information not shown below, contact your local sales office, email [graphic@arjowiggins.com](mailto:graphic@arjowiggins.com) or visit [www.arjowigginsgraphic.com](http://www.arjowigginsgraphic.com)

CYCLUSPRINT (HEAVY)					
	ISO 534	ISO 11475	ISO 8254	ISO 8791-4	ISO 2470
Weight (gsm)	Bulk (cm <sup>3</sup> g)	CIE Whiteness (%)	Gloss Lehmann %	Smoothness / PPS	ISO Brightness (%)
250	0.99	89	23	3.2	86
300	1.04	89	23	3.2	86
350	1.03	89	23	3.7	86