

Product / brand: Eural Premium

Paper Mill: Le Bourray

Country of origin: France

Website: www.arjowigginsgraphic.com

eural premium

Product Data

Eural is a range of high quality natural white 100% recycled papers, manufactured at the Papeteries du Bourray Mill in Le Mans, France. Eural is manufactured using de-inked post-consumer and post-industrial waste (the de-inked pulp is produced on site) without any bleaching processes.

Eural Premium offer outstanding qualities including excellent opacity, a smooth finish and great printability.

Naturally, Eural's services live up to your expectations.

- Eural Premium is a 100% recycled matt coated paper with a natural whiteness
- Eural Premium is available in the following weights: 60, 65, 70, 80, 90, 100, 115, 130, 150, 160, 170 and 350 gsm.

For more in-depth environmental information, please request the Environmental Declaration or visit www.arjowigginsgraphic.com

Certified Management Systems & Product certifications

For more in-depth environmental information, please request the Environmental Declaration or visit www.arjowigginsgraphic.com

- ISO 9001 (Quality Management Standard)
- ISO 14001 (Environmental Management Standard)
- OHSAS 18001 (Health and Safety Management System)
- National Association of Paper Merchants (NAPM)
- EU Ecolabel (n°FR/011/003)
- Paper By Nature
- Association des Producteurs et Utilisateurs de Papiers Recyclés (APUR)
- DIN 6738 Permanent Paper Standard
- FSC® Certified available on request

Applications

Suitable for a range of applications (depending on grammage):
Manuals, brochures, inserts, financial reports, invitations, catalogues, school exercise books, calendars, dividers, press kits, etc.
For use in exercise books, a specific treatment can be added on request.

Recommendations

Printing processes:

- Sheet fed offset, silkscreen.
- Printing inks : all inks suitable for coated paper
- Suitable for laser and inkjet personalisation
- Recommended frame = 150 to 175.
- Recommended wet pH = 5,5.

Converting:

- Suitable for gumming, sealing, perforation, film deposit, varnishing
- Folding

Technical specification

If you seek information not below, contact your local sales office, email graphic@arjowiggins.com or visit www.arjowigginsgraphic.com

EURAL PREMIUM					
	ISO 534	ISO 11475	ISO 2471	ISO 5627	ISO 8254
Weight (gsm)	Bulk (cm ³ g)	CIE Whiteness (%)	Opacity (%)	Smoothness (sec)	Gloss (%)
60	0.97	92	90	110-180	20-30
65	0.97	92	91	110-180	20-30
70	0.97	92	92	110-180	20-30
80	0.95	92	93	110-180	20-30
90	0.95	92	94	110-180	20-30
100	0.90	92	95	110-180	25-35
115	0.90	92	96	110-180	30-40
130	0.90	92	97	110-180	30-40
150	0.90	92	98	110-180	30-40
160	0.90	92	98	110-180	30-40
170	0.90	92	98	110-180	30-40
350	0.95	92	>100	110-180	20-30