

TEKNOCARD 2

THE TEKNICAL SENSATION

Teknocard 2 is a coated 2 sides premium board FSC® Mix certified for packaging and graphical applications. It is available non-recycled or 100% recycled.

Teknocard 2 guarantees outstanding bulk, stiffness and dimensional stability and is intended to deliver exceptional color reproduction and converting performance.

Teknocard 2 is a great value product with high whiteness, ultimate printability and all the laminating and embossing the market needs.



CERTIFICATIONS



The mark of responsible forestry

ECF

REACH



ISO 9706



Heavy Metal Absence



APPLICATIONS

Suitable for a wide range of graphical and packaging applications.

Graphical Print :

Business cards, greeting cards, business cards, brochures, paperback book and report covers, postcards, tags and folders.

Packaging :

Cosmetics, perfume, pharmaceutical, CD inserts, DVD covers, chocolates and premium food and non food products.

For more in-depth environmental information, please download the Environmental Declaration on www.arjowigginsgraphic.com.

TECHNICAL SPECIFICATIONS

If you seek samples or information not shown below, contact your local sales office, email julie.brannen@arjowiggins.com or teknocard@arjowiggins.com.

CALIPER	BASIS WEIGHT 24 x 36	COVER WEIGHT 20 x 26	GSM	BRIGHTNESS		
				ISO	GE	GLOSS
10	147	89	240	96	92.5	45
11	160	96	260	96	92.5	45
12	172	103	280	96	92.5	45
13	184	111	300	96	92.5	45
14	203	122	330	96	92.5	45
15	215	129	350	96	92.5	45
17	246	148	400	96	92.5	45

RECOMMENDATIONS

Prepress recommendations :

- Screen rulings (Max 200 lpi)
- For heavy ink loads, Under-colour-removal (UCR) recommended

Printing recommendations :

- Guaranteed for Offset litho
- Sheets suitable for silk screen printing
- Suitable for use in mono and color laser printers
- Compatible with IR-drying and UV-curing
- Suitable for offset varnishes, acrylic and UV
- Suitable for gravure

Converting recommendations :

- Suitable for foil lamination, hot-foil blocking / cold foil blocking
- Suitable for blind embossing - avoid sharp edges on tools
- Suitable for hot-foil blocking / cold foil blocking
- Suitable for die cutting and perforation
- Folding pre-creasing recommended
- Suitable for clamps, wire thread and adhesive binding

This information is supplied in good faith and is accurate at the date of publication. Arjowiggins Graphic reserves the right to change or update information as deemed necessary.

Fully compatible with all digital presses :

Certified for
HP Indigo

DRY
Toner

Manufactured by:

 arjowiggins

graphic papers